

BPTD
Bandlock® Pro gängspännare

Bandlock® Pro BPTD gängspännare används till att förankra takkonstruktionen till en gjuten M12 gängstång. Med det nya innovativa klicksystemet sparar användaren mycket tid i montering jämfört med traditionella bandsträckare. BPTD kan användas med 25 och 40 mm vinddragband

Egenskaber

Material

- Stålkvalitet:
Galvaniserat stål S250GD + Z275 enligt EN 10346
- Korrosionsskydd:
275 g/m² på båda sidorna motsvarande en zinktjocklek på cirka 20 µm





Fördelar

- Enkel monering
- Inga lösa delar som: skuvar eller muttrar
- Tidsbesparande jämfört med traditionella bandsträckare
- Kan användas med 25 och 40 mm vinddragband
- Lätt att förstå

Användning

Applikationer

Tillavstyvning och förankring av takkonstruktioner




BPTD
Bandlock® Pro gängspännare



Teknisk data

Mått



Art. nr.	Mått [mm]			Antal / frp
	A	B	t	
BPTD	51	180	2.5	10
BPTD-HV	51	180	2.5	50

Product capacities

Art. nr.	Threaded rod	Product capacities
		Characteristic capacities [kN]
BPTD	M12	R _{1,k} 27.5

The values are whith all 6 pins in use and 2 bended

BPTD

Bandlock® Pro gängspännare

Montering

Fixing

- The BPTD must be fastened at least 10 mm onto the threaded rod
- Connect the windbracing strap to the BPTD and click the connector shut
- Bend the 2 longest pins
- Screw the BPTD further onto the threaded rod to tighten the tension strap.
- **IMPORTANT** - by installation of 60 mm straps, the corners of the strap has to be trimmed so that all 6 pins in the tightener can be used, see installation pics below.

