



They are designed for concealed connections between timber members and concrete. The number of dowels and anchors can be chosen free, depending on the applied load. BTC concealed beam hangers are approved to take load in all 3 directions. Therefore beam connections with a roof pitch can also be built in a easy and safety way.



[ETA-07/0245](#), [UK-DoP-e07/0245](#)

### FEATURES



### Material

#### Steel:

S 250 GD +Z 275 acc. EN 10326

#### Corrosion protection:

275 g/m<sup>2</sup> on both sides - correspond to a zinc layer of approx. 20 µm

### Benefits

- The variety of connection options are given in the ETA 07/0245, here you will find also information of:
- densities > 350kg/m<sup>3</sup>
- different slopes
- smaller timber widths
- other CNA nails / CSA screws
- connections of concrete
- connections to headers, wich are free to rotate

### APPLICATIONS

#### Suitable On

#### Supporting member:

concrete, steel

#### Supported member:

solid wood, engineered wood

### Scope


- The beam hangers serve as concealed connections of joists to the main beams or columns.
- connections with slopes up to 45 ° can be performed.

TECHNICAL DATA

Product Dimensions

References	Joist Size [mm]	Product Dimensions [mm]					Header holes	Joist holes
	Height Min	A	B	C	t <sub>1</sub>	t <sub>2</sub>	Ø14	Ø13
BTC120-B	160	120	128	96	3	6	2	3
BTC160-B	200	160	128	96	3	6	4	4
BTC200-B	240	200	128	96	3	6	4	5
BTC240-B	280	240	128	96	3	6	4	6
BTC280-B	320	280	128	96	3	6	6	7
BTC320-B	360	320	128	96	3	6	6	8
BTC360-B	400	360	128	96	3	6	6	9
BTC400-B	440	400	128	96	3	6	8	10
BTC440-B	480	440	128	96	3	6	8	11
BTC480-B	520	480	128	96	3	6	8	12
BTC520-B	560	520	128	96	3	6	8	13
BTC560-B	600	560	128	96	3	6	8	14
BTC600-B	640	600	128	96	3	6	8	15

Wood/rigid substrate fastening - Characteristic values in kN



References	Number of Fasteners				Product characteristic capacities - Timber C24 [kN]											
	Header		Joist		R <sub>1,k</sub>						R <sub>2,k</sub>					
	Qty	Type	Qty	Type	Dowels length [mm]						Dowels length [mm]					
					80	100	120	140	160	180	80	100	120	140	160	180
BTC120-B	2	Ø 12	3	STD12	11.5	12.7	14.2	15.8	17.2	17.2	7.7	8.5	9.5	10.5	11.5	11.5
BTC160-B	4	Ø 12	4	STD12	18.5	20.4	22.8	25.3	27.8	27.8	13.9	15.3	17.1	19	20.9	20.9
BTC200-B	4	Ø 12	5	STD12	26.7	29.4	32.7	36.4	40.3	40.3	21.4	23.5	26.2	29.1	32.2	32.2
BTC240-B	4	Ø 12	6	STD12	35.8	39.4	43.8	48.6	53.8	54.3	29.8	32.8	36.5	40.5	44.8	45.3
BTC280-B	6	Ø 12	7	STD12	45.6	50.1	55.6	61.7	68.3	69.4	39.1	42.9	47.7	52.9	58.5	59.5
BTC320-B	6	Ø 12	8	STD12	56	61.4	68.1	75.5	83.4	85.5	49	53.7	59.6	66.1	73	74.8
BTC360-B	6	Ø 12	9	STD12	66.8	73.1	80.9	89.6	99	102.2	59.4	65	71.9	79.6	88	90.8
BTC400-B	8	Ø 12	10	STD12	77.9	85.1	94	104.1	114.8	119.5	70.1	76.6	84.6	93.7	103.3	107.6
BTC440-B	8	Ø 12	11	STD12	89	97.2	107.3	118.7	130.9	133.3	81	88.4	97.5	107.9	119	121.2
BTC480-B	8	Ø 12	12	STD12	100.5	109.5	120.7	133.4	147	147	92.1	100.4	110.6	122.3	134.8	134.8
BTC520-B	8	Ø 12	12	STD12	100.5	109.5	120.7	133.4	147	147	100.5	109.5	120.7	133.4	147	147
BTC560-B	8	Ø 12	12	STD12	100.5	109.5	120.7	133.4	147	147	100.5	109.5	120.7	133.4	147	147
BTC600-B	8	Ø 12	12	STD12	100.5	109.5	120.7	133.4	147	147	100.5	109.5	120.7	133.4	147	147

For load combination:


$$\sum \left( \frac{F_{i,d}}{R_{i,d}} \right)^2 \leq 1$$

R<sub>2,k</sub> capacities are calculated as R<sub>2,k</sub> = R<sub>1,k</sub> x (nb of dowels - 1) / (nb of dowels).

The top dowel is not considered for the uplift capacities as it is placed in an open hole.

The anchors resistance and their number have to be checked according to the ETA and the type of header. The number of anchors given in the table is the maximum. If their resistance is decisive, it is the resistance to consider for the connection.

**Product characteristic capacities - Timber beam to rigid support - R3.k and R4.k**



References	Number of Fasteners				Product characteristic capacities - Timber C24 [kN]								Number of Fasteners				Product Characteristic Capacities - Timber C24 [kN]
	Header		Joist		R <sub>3,k</sub>								Header		Joist		R <sub>4,k</sub>
	Qty	Type	Qty	Type	Dowels length [mm]								Qty	Type	Qty	Type	
					60	80	100	120	140	160	180						
BTC120-B	2	Ø 12	3	STD12	2.6	2.9	3.5	4	4.5	5.2	5.3	2	Ø 12	3	STD12	6,7/kmod	
BTC160-B	4	Ø 12	4	STD12	3.2	3.9	4.4	5	5.9	6.5	7	4	Ø 12	4	STD12	13,4/kmod	
BTC200-B	4	Ø 12	5	STD12	4	4.9	5.5	6.3	7.2	7.8	8.8	4	Ø 12	5	STD12	13,4/kmod	
BTC240-B	4	Ø 12	6	STD12	4.8	5.7	6.6	7.5	8.4	9.1	10.4	4	Ø 12	6	STD12	13,4/kmod	
BTC280-B	6	Ø 12	7	STD12	5.6	6.5	7.6	8.7	9.6	10.4	11.9	6	Ø 12	7	STD12	20,1/kmod	
BTC320-B	6	Ø 12	8	STD12	6.4	7.3	8.6	9.7	10.8	11.8	13.4	6	Ø 12	8	STD12	20,1/kmod	
BTC360-B	6	Ø 12	9	STD12	7.2	8.1	9.5	10.8	12	13.2	14.9	6	Ø 12	9	STD12	20,1/kmod	
BTC400-B	8	Ø 12	10	STD12	8	8.9	10.5	11.9	13.2	14.7	16.4	8	Ø 12	10	STD12	26,8/kmod	
BTC440-B	8	Ø 12	11	STD12	8.8	9.7	11.4	13	14.4	16.1	17.8	8	Ø 12	11	STD12	26,8/kmod	
BTC480-B	8	Ø 12	12	STD12	9.6	10.6	12.4	14.1	15.6	17.6	19.3	8	Ø 12	12	STD12	26,8/kmod	
BTC520-B	8	Ø 12	12	STD12	10.4	11.4	13.3	15.1	16.8	19.1	20.8	8	Ø 12	12	STD12	26,8/kmod	
BTC560-B	8	Ø 12	12	STD12	11.2	12.3	14.3	16.2	18	20.5	22.3	8	Ø 12	12	STD12	26,8/kmod	
BTC600-B	8	Ø 12	12	STD12	12	13.2	15.2	17.3	19.2	22	23.8	8	Ø 12	12	STD12	26,8/kmod	

The anchors resistance and their number have to be checked according to the ETA and the type of header. The number of anchors given in the table is the maximum. If their resistance is decisive, it is the resistance to consider for the connection.

## INSTALLATION

### Fixing

The following fasteners need to be used:

- steel dowels  $\varnothing 12$  mm, length acc. width of the joist
- bolts M12 acc. static requirements

