



Pads of various sizes are designed to suit the products Simpson Strong-Tie®.

## FEATURES




## Material

- **AH29050/2-FR:** galvanized steel S250GD + Z275 according to NF EN 10346.
- **US40/50/10G washer:** steel S235JR + hot-dip galvanized finish.

## Benefits

- Low-width anchor for use in frame uprights 45 mm wide.
- Anchors the wood-frame wall solidly into the ground (recommended in seismic zones).
- Reinforces the upright-lower plate connection by preventing the uplift of the upright.

Thus, energy is dissipated in the panel through the stitching.



## APPLICATIONS

### Applicable materials


Wood, wood products, steel

### Application area

- Load distribution in surface tension rods or angle

TECHNICAL DATA

Dimensioner



References	DB nr.	NOBB nr.	Dimensioner [mm]			
			A	B	Tykkelse	Holes
US40/50/10G-B	7742588	21744487	40	50	10	13,5x25

## INSTALLATION

### Installation

- Det er vigtigt at underlagsskiven vælges og vendes således, at skiven er tæt på beslagets bukketkant




Fig. 1:  
Installation  
med 1 plade i  
bunden, 45 mm




Fig. 2:  
Installation  
med 2 plader i  
bunden, 45 mm




Fig. 3:  
Installation af  
indvendig væg

