



Suitable for marine environments and industrial atmospheres. The TTFA4 screw will not discolour the woodwork around the screw head. Also suitable for precious woods such as oak, cedar or larch. The screw has a 6 lobe recess to ensure good grip and a cutpoint, which effectively drives the screw into the woodwork and counteracts splitting.

#### OMINAISUUDET



#### Features

- 6 lobe drive.
- Flat head with nibs.
- Coarse thread.
- Type 17 point.
- Marine grade stainless steel (A4).




#### SOVELLUS

#### Suitable for

- Decking to timber.
- Precious woods including oak, cedar and larch.

TECHNICAL DATA

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	NOBB nr.	Mitat [mm]					
			d	l	d <sub>h</sub>	l <sub>g</sub>	t <sub>fix</sub>	Bit
TTFA44.2X35T-20	74385	53293743	4.2	35	7	20	14	T-20
TTFA44.2X45T-20	74386	53293758	4.2	45	7	23	22	T-20
TTFA44.2X55T-20	74387	53295366	4.2	55	7	27.5	27.5	T-20
TTFA44.8X75T-20	74389	53293762	4.8	75	7	35	40	T-20
TTFA44.2X45PH2	74291	53293622	4.2	45	7	23	22	PH2
TTFA44.2X55PH2	74292	53293637	4.2	55	7	27.5	27.5	PH2

Tuotteen ominaisuudet



Tuotenro	Tuotteen ominaisuudet			
	Taivutuslujuus - M <sub>y,k</sub> [M <sub>y,k</sub> ] [Nmm]	Tyypillinen vetoparametri - f <sub>ax,k,90°</sub> [f <sub>ax,k,90°</sub> ] [N/mm <sup>2</sup> ]	Tyypillinen läpivetoparametri - f <sub>head,k</sub> [f <sub>head,k</sub> ] [N/mm <sup>2</sup> ]	Tyypillinen vetolujuus - f <sub>tens,k</sub> [f <sub>tens,k</sub> ] [kN]
TTFA44.2X35T-20	2575	17	20.4	4.2
TTFA44.2X45T-20	2575	17	20.4	4.2
TTFA44.2X55T-20	2575	17	20.4	4.2
TTFA44.8X75T-20	4371	20.7	16.4	5.6
TTFA44.2X45PH2	2575	17	20.4	4.2
TTFA44.2X55PH2	2575	17	20.4	4.2

