



O parafuso para terraços DSPIX4 - Impreg®X4 é recomendado para a realização de terraços exteriores em madeira exótica.



#### OMINAISUUDET



#### Features

- 6 Lobe drive
- Cap head
- Coarse thread
- Type 17 point
- Impreg® X4 coating





#### SOVELLUS

#### Suitable for

- Decking boards to wood

TECHNICAL DATA

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	NOBB nr.	Mitat [mm]					
			d	l	d <sub>h</sub>	l <sub>g1</sub>	l <sub>g2</sub>	Bit
DSPIX44.8X60	74356	53293705	4.8	60	6.5	26	12	T-20
DSPIX44.8X70	74357	53293713	4.8	70	6.5	32	18	T-20
DSPIX45.5X80	74358	53293724	5.5	80	7	37.5	20	T-25
DSPIX46.5X95	74359	53293732	6.5	95	8	40	29	T-30

Tuotteen ominaisuudet

Tuotenro	Taivutuslujuus - M <sub>y,k</sub> [Nmm]	Tyypillinen vetoparametri - f <sub>ax,k,90°</sub> [N/mm <sup>2</sup> ]	Tyypillinen läpivetoparametri - f <sub>head,k</sub> [N/mm <sup>2</sup> ]	Tyypillinen vetolujuus - f <sub>tens,k</sub> [kN]	Vääntösuhde
DSPIX44.8X60	5951	15.1	32.2	7.9	1.8
DSPIX44.8X70	5951	15.1	32.2	7.9	1.8
DSPIX45.5X80	11193	15.7	33.3	12.2	1.8
DSPIX46.5X95	13203	15.8	45.7	12.9	1.5

