



Made for hardwood decking such as Cumaro, Bankirai and others. Can be used in Marine environments. Needs pre-drilling with 4 mm drill and pre-countersinking close to the edge.



OMINAISUUDET



Features:

- 6 lobe drive
- Double threaded
- Chisel point




SOVELLUS

Applications:

- Hardwood decking boards to wood

TECHNICAL DATA

Mitat



Tuotenro	Article number	NOBB	Mitat [mm]					Bit	Cond.	m ² / box
			d	l	d _h	l _{g1}	l _{g2}			
DSPROA45.5X50	74287	53293777	5.5	50	7	22.5	10.5	T-25	150	4.4
DSPROA45.5X60	74288	53293781	5.5	60	7	27.5	10.5	T-25	150	4.4
DSPROA45.5X70	74289	53293796	5.5	70	7	32.5	10.5	T-25	150	4.4
DSPROA45.5X80	74290	53293800	5.5	80	7	37.5	10.5	T-25	150	4.4

Product characteristic properties

Tuotenro	Yield Moment M _{y,k} [Nm]	Withdrawal Parameter f _{ax,k} [N/mm ²]	Head Pull Through Parameter f _{head,k} [N/mm ²]	Characteristic Tensile Capacity f _{tens,k} [kN]	Torsional ratio
DSPROA45.5X50	7585	12.8	31.8	7.8	3.8
DSPROA45.5X60	7585	12.8	31.8	7.8	3.8
DSPROA45.5X70	7585	12.8	31.8	7.8	3.8
DSPROA45.5X80	7585	12.8	31.8	7.8	3.8

Technical data sheet

DSPROA4 - HARDWOOD DECKING SCREW - STAINLESS STEEL

A4



Hedgaardsvej 11 8300 Odder
tel: +45 8781 7400 / fax : +45 8781 7409

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.

DSPROA4 - Hardwood Decking Screw -
Stainless Steel A4

page
3/3

2021-09-14

www.strongtie.fi