



Used indoors for fitting kitchen units and wooden battens to porous masonry materials without pre-drilling. However when fixing to Leca, pre-drilling of a hole 1 mm less than the relevant plug diameter is required. Pre-drill the material that is to be fixed, knock in the plug with a hammer, turn no more than six turns, and the plug will expand, like a knot.

OMINAISUUDET



Features:

Used indoors for fitting kitchen units and wooden battens to porous masonry materials without pre-drilling. However when fixing to Leca, pre-drilling of a hole 1 mm less than the relevant plug diameter is required. Pre-drill the material that is to be fixed, knock in the plug with a hammer, turn no more than six turns, and the plug will expand, like a knot.

SOVELLUS

Application:

- Wood to lightweight concrete

TECHNICAL DATA

Product dimensions



Tuotenro	Item code	NOBB nr.	Fastener dimensions [mm]					
			d	l	d _h	l _g	t _{fix}	bit
LBP6.0x50	75529	55840706	6	50	-	-	15	T-20
LBP6.0x70	75530	55840714	6	70	-	-	35	T-20
LBP8.0x60	75531	55836718	8	60	11	-	10	T-25
LBP8.0x80	75532	55840695	8	80	11	-	30	T-25
LBP8.0x100	75533	55842795	8	100	11	-	50	T-25
LBP8.0x120	75534	55841834	8	120	11	-	70	T-25
LBP8.0x140	75535	55841845	8	140	11	-	90	T-25
LBP10.0x100	75536	55841853	10	100	-	-	40	T-40
LBP10.0x120	75538	55841872	10	120	-	-	60	T-40
LBP10.0x140	75537	55841864	10	140	-	-	80	T-40
LBP10.0x460	75539	55841883	10	460	-	-	400	T-40

