



Made for hardwood decking such as Cumaro, Bankirai and others. Can be used in Marine environments. Needs pre-drilling with 4 mm drill and pre-countersinking close to the edge.

[UK-DoP-h17-0016-S1.0.pdf](#)



FEATURES



Material

- Stainless Steel A4

Features:

- 6 lobe drive
- Double threaded
- Chisel point





APPLICATIONS

Applications:

- Hardwood decking boards to wood

TECHNICAL DATA

Dimensions and drill holes



References	Article number	Dimensions and drill holes [mm]						Bit	Cond.	m ² / box
		d	l	d _h	d ₁	l _{g1}	l _{g2}			
DSPROA45.5X50	74287	5.5	50	7	3.8	22.5	10.5	T-25	150	4.4
DSPROA45.5X60	74288	5.5	60	7	3.8	27.5	10.5	T-25	150	4.4
DSPROA45.5X70	74289	5.5	70	7	3.8	32.5	10.5	T-25	150	4.4
DSPROA45.5X80	74290	5.5	80	7	3.8	37.5	10.5	T-25	150	4.4

Product characteristic properties

References	Yield Moment M _{y,k} [Nm]	Withdrawal Parameter f _{ax,k} [N/mm ²]	Head Pull Through Parameter f _{head,k} [N/mm ²]	Characteristic Tensile Capacity f _{tens,k} [kN]	Torsional ratio
DSPROA45.5X50	7585	12.8	31.8	7.8	3.8
DSPROA45.5X60	7585	12.8	31.8	7.8	3.8
DSPROA45.5X70	7585	12.8	31.8	7.8	3.8
DSPROA45.5X80	7585	12.8	31.8	7.8	3.8

