



Hot dip galvanized plastic coil collated CNA connector nails fit in most common nail guns on the market with a angle of the nail of 15-16°.



FEATURES



OUTDOOR

GALVA

Advantages

- The conical shape under the head ensures that the nail is fully in contact with the hole
- High withdrawal capacity
- Hot dip galvanized
- Annular ring thread
- Plastic coil 15-16°


APPLICATIONS

Support

- Connectors to wood

TECHNICAL DATA

Product dimensions



References	Item Nr.	DB nr.	Fastener dimensions					Qty per coil	Qty per box
			d	l	lg	dh	ht		
CNAC15G4.0X4	76142	2124154	4	40	25	7	1.5	100	1200
CNAC15G4.0X50	76143	2124155	4	50	35	7	1.5	100	1200
CNAC15G4.0X6	76144	2124156	4	60	45	7	1.5	100	1200

Characteristic capacities

References	Characteristic capacities - Timber C24 acc to ETA-04/0013 [kN]	
	R _{ax,k}	R _{lat,k}
CNAC15G4.0X40	0.7	1.9
CNAC15G4.0X50	1	2.2
CNAC15G4.0X60	1.2	2.4

Capacities are for 2mm thick steel plates and Grade C24 timber. Please refer to ETA-04/0013 for capacities of other thickness and timber grades

