



CSA connector screw is developed for installing Simpson Strong-Tie connectors to timber, in order to obtain the published load bearing capacities. The conical shape under the head ensures a full contact with the connector which increases the transfer of force. A fixed connection with larger cross-bearing capacity than for standard screws is obtained. The 6 lobe recess helps to fix the screw during insertion.



[ETA-04/0013](#), [UK-DoP-e04/0013](#)



## FEATURES



### Material

- Steel - Electro galvanised coating

### Features

- ETA approved (ETA-04/0013)
- 6 lobe drive
- Conical shape under the head for secure fit in connector holes
- Type 17 point to prevent splitting of timber

## APPLICATIONS

### Suitable On

- **Supporting / Supported member:** solid wood, composite lumber, glued-laminated wood.



### Common Applications

Fixing connectors to timber:

- Joist hangers
- Angle brackets
- Straps

TECHNICAL DATA

Product Dimensions



References	Tun / DB nr.	NOB nr.	Fastener dimensions [mm]				
			l	lg	d <sub>1</sub>	d	d <sub>h</sub>
CSA5,0X35	1244280	41467671	35	29	3.15	4.85	8.3
CSA5,0X40	1244295	41467762	40	34	3.15	4.85	8.3
CSA5,0X50	1245787	41467770	50	44	3.15	4.85	8.3

Capacities are given for 2mm steel plate thickness and C24 timber. To determine the capacities for other steel thickness and / or timber grades, please refer to ETA-04/0013.

Performance values based upon timber density of 350 kg/m<sup>3</sup>

