



**Bandschroeven CSA** vereenvoudigen de plaatsing van hoekijzers en verbinders op houten ondergrond. De kegelvormige kop garandeert een nauwsluitende passing met de verbinder voor een betere krachtsoverdracht.



[ETA-04/0013](#), [NL-DoP-e04/0013](#)

### KENMERKEN



### Materiaal

- Afwerking wit verzinkt.

### Voordelen

- Dankzij de houtspecifieke schroefdraad wordt het dragermateriaal snel en eenvoudig ingesneden,
- Geen houtspijting,
- Karakteristieke belastingwaarden overeenkomstig Eurocode 5 (afschuifsterkte en uittreksterkte),
- CE-markering overeenkomstig EN 14592.



## TOEPASSINGEN

### Ondergrond




- **Drager** : massief hout, compositiehout, gelijmd gelamineerd hout,
- **Gedragen bouwdeel**: massief hout, compositiehout, gelijmd gelamineerd hout.

### Toepassingsgebieden

- Ophangbeugels voor kapconstructies,
- Verbindingshoekijzers,
- Bandijzer.

TECHNISCHE GEGEVENS

Product dimensions and capacities



Referentie	Afmetingen bevestigingen [mm]						m <sup>2</sup> /doos [r/min]	Karakteristieke waarden - Hout C24 overeenkomstig ETE-04/0013 [kN]	
	d	l	d <sub>h</sub>	d <sub>1</sub>	l <sub>g</sub>	Bit		R <sub>lat,k</sub>	R <sub>ax,k</sub>
CSA5,0X35T	4.85	35	8.3	3.15	29	T25	2500	1.99	2.11
CSA5,0X50T	4.85	50	8.3	3.15	44	T25	2500	2.63	3.2

Capacities are given for 2 mm steel plate thickness and C24 timber. To determine the capacities for other steel thickness and / or timber grades, please refer to ETA-04/0013.

