



BAN09 windbracing straps can be used for anchoring and bracing of roof constructions. The engineered "strong-holes" ensures a very light 0,9 mm strap with the same capacities as a 2 mm strap. The thin material makes the strap easy to lift and handle on the job site. And it is easy to cut with metal shears.

Характеристики



Материал

Оцинкованная сталь DX51D. Покрытие Z275



Преимущества

- Reinforced holes offer enhanced strap tensile capacity
- Very lighth weigt but strong
- Easy to cut with metal shears



TECHNICAL DATA

Размер



Артикул	Размер			Отверстия
	A [mm]	B [m]	t [mm]	Ø
BAN094012	40	12	0.9	5
BAN094025	40	25	0.9	5

Thinner bands mean greater elongation, therefore it is recommended to assess the deformations that may occur due to the 0.9 band extension using band lengths over 6 m.

Product capacities

Артикул	Characteristic capacities $R_{1,k}$ Timber C24 [kN]				
	Maximum value	CNA4.0x35	CNA4.0x40	CNA4.0x50	CNA4.0x60
BAN094012	17.8	1.68 x n	1.83 x n	2.22 x n	2.36 x n
BAN094025	17.8	1.68 x n	1.83 x n	2.22 x n	2.36 x n

n = effective number of nails in the row according to Eurocode 5 – 8.3.1.1 (8)

Установка

Fixation

Оцинкованная сталь DX51D. Покрытие Z275

